

MAIN FEATURES

Forged chambers
Laser welded diaphragm
Optional exotic materials

SUGGESTED APPLICATIONS

Separation systems
Isolation applications
Viscous & corrosive media
High-pressure applications
High vibration application



FLANGED SEAL FLUSHED DIAPHRAGM

BASIC DESCRIPTION

Flange design : ANSI B40.2
Seal Range : -1 up to 250 bar
Storage temperature : -40...+65°C
Service temperature : 370°C max.
Weld joints : Laser welding for Diaphragm and
TIG argon arc welding for other parts

MATERIAL OF CONSTRUCTION

Sensing element : Diaphragm
Top chamber material: SS 304 / SS 316
Diaphragm : SS 316L / Monel / HC-276 / INC-625 /
Titanium / Tantalum
Bottom chamber material : SS 304 / SS 316 / SS 316L /
Monel / HC-276 / INC-625 / Titanium
Capillary : SS 304 / SS 316
Armour : SS 304 / SS 316 / PVC

PRODUCT SPECIFICATION

Seal type : Welded [Model: **641T/641F**]
Instrument connection : 1/2" NPT (F) / 1/2" BSP (F)
Sealing fluid : Silicon Oil [-40...250°C]
Process connection : 1" - 3" Flange sizes

PROTECTION ON WETTED PARTS


PTFE coating on diaphragm [Code : CB]
Material : PFA - 70 Micron thick [spray coated & oven cured]
Service temperature : 300°C max.

PTFE lining on bottom chamber [Code : LB]

FILLING LIQUIDS Vs TEMPERATURE RANGE

CODE	Fluid Name	Temperature Range
L2	Silicon Oil	-40°C to 250°C
L3	Food Grade Oil	-20°C to 200°C
L4	Hi-Temp Silicon Oil	-20°C to 450°C
L5	Fluorinated Oil	-10°C to 350°C

DIMENSIONAL DRAWINGS



MODEL : 641T/641F

All dimensions are in mm.

MODEL CODING

MODEL	-	TOP CHAMBER	DIAPHRAGM	BOTTOM CHAMBER	/	INSTRUMENT CONNECTION	PROCESS CONNECTION	/	SEALING LIQUID	/
641T/641F = Welded Flanged Seal		S04 = SS 304 S16 = SS 316	S6L = SS 316L M40 = Monel 400 H76 = Hastelloy C-276 N62 = Inconel 625 TT6 = Titanium TAT = Tantalum	S16 = SS 316 S6L = SS 316L M40 = Monel 400 H76 = Hastelloy C-276 N62 = Inconel 625 TT6 = Titanium		F4N = ½" NPT (F) F4B = ½" BSP (F)	FX = Select from the table below.		L2 = Silicon Oil L3 = Food Grade Oil L4 = Hi-Temp Silicon Oil L5 = Fluorinated Oil	

CAPILLARY	CAPILLARY LENGTH	/	OTHER OPTIONS
C1 = No Capillary C2 = SS 316L bore + SS 304 Armour C3 = SS 316L bore + SS 316 Armour C4 = SS 316L bore + SS 304 Armour + PVC coating	1 Mtr. up to 6 Mtr. Other length on request		MTC = Material test certificate, 3.1 CC = 5-point factory calibration certificate TS6 = SS 316 tag plate TS4 = SS 304 tag plate LB = PTFE lining on Bottom Chamber CD = Coating on Diaphragm

FLANGE TABLE

ANSI B 16.5																	
Code	Size	Rating	Code	Size	Rating	Code	Size	Rating	Code	Size	Rating	Code	Size	Rating	Code	Size	Rating
F01	½"	150#	F02	½"	300#	F03	½"	600#	F04	½"	900#	F05	½"	1500#	F06	½"	2500#
F07	¾"	150#	F08	¾"	300#	F09	¾"	600#	F10	¾"	900#	F11	¾"	1500#	F12	¾"	2500#
F13	1"	150#	F14	1"	300#	F15	1"	600#	F16	1"	900#	F17	1"	1500#	F18	1"	2500#
F25	1½"	150#	F26	1½"	300#	F27	1½"	600#	F28	1½"	900#	F29	1½"	1500#	F30	1½"	2500#
F31	2"	150#	F32	2"	300#	F33	2"	600#	F34	2"	900#	F35	2"	1500#	F36	2"	2500#
F43	3"	150#	F44	3"	300#	F45	3"	600#	F46	3"	900#	F47	3"	1500#	F48	3"	2500#

ORDERING EXAMPLE 641T/641F-S6L-S16-F4N-F33-L2.

QUICK ORDER DETAILS / FEEDBACKS